

CobiCabling CAT 5e Shielded Keystone Jack



(indicative image only)

Features:

100MHz working frequency (CAT5e, Class D)

25-years manufacturers warranty

Fully shielded design

Connections coding according to TIA 568A and 568B

26-23 AWG, solid or stranded

Toolless termination

PRODUCT DESCRIPTION

CobiCabling CAT5e Toolless Keystones are designed for quick and reliable installation in mind. With a small total diameter it permits several cable entry options as well as several housing options from patchpanels, faceplates and shutters to sub floor boxes.

CONFORMS TO:

- EN 50173-1:2018-07
- EN 50173-1:2011
- ISO/IEC 11801 Edition 2.2
- ANSI/TIA-568-C.0
- ANSI/TIA-568-C.1
- ANSI/TIA-568-C.2
- IEC 60603-7

TYPICAL APPLICATIONS:

- 100Base-TX Fast Ethernet;
- 1000Base-T Gigabit Ethernet;
- PoE, PoE+, 4PPoE and Power over HDBaseT (POH) applications up to 100 Watts

Technical spec	Details
Dimensions (±0,2mm)	Width: 16,8mm, Height: 21,7mm, Depth: 37,8mm
Type of connector	RJ45
Category	5e (Backward compatibility)
Types of shielding	STP (Screened)
Housing	Die cast Zinc-alloy
Conductor diameter	26-23 AWG

Part numbers	Name
C21-5000	CobiCabling CAT 5e Shielded Keystone Jack