


CobiCabling CAT 5e U/UTP Cable LSOH 200MHz, 4x2xAWG24



Features:

200MHz working frequency (CAT5e, Class D)

25-years manufacturers warranty

Sequential metre markings

LSOH outer sheath

Euroclass Dca- s2,d2,a1

PRODUCT DESCRIPTION

CobiCabling Category 5e cable unshielded LSOH cable is manufactured and tested to exceed EN 50173-1:2018-07, EN 50173-1:2011, ISO/IEC 11801 Edition 2.2 with exceptional margin on all parameters. Our Cat5e cable is designed for high speed LAN applications including Gigabit Ethernet, combined with our patch panels and connectivity product it forms a truly reliable foundation for any network.

CONFORMS TO:

- EN 50173-1:2018-07
- ISO/IEC 11801 Edition 2.2
- ANSI/TIA-568-C.0/C.1/C.2
- IEC 60754-2

TYPICAL APPLICATIONS:

- 100Base-TX Fast Ethernet;
- 1000Base-T Gigabit Ethernet;
- Composite Video;
- ATM-25/52/155 Mbit/s, Token Ring

Technical spec	Details
Frequency	Tested up to 200MHz
Outer sheath	LSOH
Category compliance	5e
Shield	U/UTP (unshielded cable)
Metre mark	From 305 to 0 (every 1m)
NVP	69% (0,69)
Overall diameter	4,8mm
Conductor diameter	24AWG
Euroclass	Dca- s2,d2,a1
Temperature range	During installation -10°C to +50°C, After installation -30°C to +70°C

Part numbers	Name
C13-5300	CobiCabling CAT 5e U/UTP Cable LSOH 200MHz, 4x2xAWG24